



# IPC

BY TENNANT COMPANY

PURE WATER CLEANING SYSTEM

## HPE HIGH PURE

PRESSURE

8~10 bar

FLOW RATE

~ 7 l/min



THIS MODEL  
CAN BE COMBINED WITH:  
IDAF40884 -  
PW-C40 D1005P4 M  
PAG. 50

### EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP
- ▶ MANOMETER

### MOST FREQUENTLY USE

#### CONSTRUCTION INDUSTRY



#### GREEN ENERGIES



#### NAUTICAL/AUTO/TRANSPORTS



#### GREENHOUSES/GLASSHOUSES/ TENSILE STRUCTURES



### TECHNICAL DATA

Code

**HPE**  
APTA40015

PERFORMANCE

Operating pressure	bar	8~10
Pure water flow	l/min	~7
Water in/out connections	gas	3/4"
Maximum working height	m	16 (also with 2 poles)
Productivity	m <sup>2</sup> /h	up to 200
Power supply	Ph-V-Hz	1-230-50
Absorbed power	kW	0,6
Dimension (LxWxH)	cm	53x50x127
Weight	kg	53

### STANDARD EQUIPMENT

CODE: FTAC40002  
REVERSE OSMOSIS  
MEMBRANE



CODE: PRCH40034  
POWDER FOR  
OSMOTIC MEMBRANE  
FILTER MAINTENANCE



CODE: KTRI40106  
FILTER KIT: - 1 pcs  
sediment filter - 1 pcs  
active carbon filter - 1 pcs  
deionizing resin cartridge



CODE: VVSF40018  
FLOW REGULATION  
VALVE



CODE: TBFX40009  
30 m FLEXIBLE HOSE  
WITH FITTINGS



CODE: CNPR40007  
GASKET LUBRICANT



CODE: AZMC40006  
HAND-HELD TDS  
METER



CODE: TBFX40010  
DRAINAGE TUBE

